















## // 081AE

**Oxygen 20 bar (300 psi)****Tube:** black synthetic elastomer.**Reinforcement:** high tensile textile cords.**Cover:** blue synthetic elastomer - abrasion and ozone resistant.**Application:** oxygen.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	13,00	0,51	20	300	60	900	48,0	1,89		0,140	0,10
8,0	5/16"	15,00	0,59	20	300	60	900	64,0	2,52		0,170	0,12
10,0	3/8"	17,00	0,67	20	300	60	900	80,0	3,15		0,205	0,14








## // 081AH

**Acetylene 20 bar (300 psi)****Tube:** black synthetic elastomer.**Reinforcement:** high tensile textile cords.**Cover:** red synthetic elastomer - abrasion and ozone resistant.**Application:** acetylene.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	13,00	0,51	20	300	60	900	48,0	1,89		0,140	0,10
8,0	5/16"	15,00	0,59	20	300	60	900	64,0	2,52		0,170	0,12
10,0	3/8"	17,00	0,67	20	300	60	900	80,0	3,15		0,205	0,14

## // 088AI

**LPG-natural gas 25 bar (375 psi)****Tube:** black synthetic elastomer.**Reinforcement:** high tensile textile cords.**Cover:** orange synthetic elastomer - abrasion and ozone resistant.**Application:** LPG-natural gas.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
8,0	5/16"	15,00	0,59	25	375	75	1100	64,0	2,52		0,170	0,12
10,0	3/8"	17,00	0,67	25	375	75	1100	80,0	3,15		0,200	0,14