

→ ⊙ ←		→ ⊙ ←		⊙		⌒) (Ⓜ	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
5	3/16	12	0,47	16	240	50	2,00		0,130	0,087	
6	1/4	13	0,51	16	240	60	2,50		0,150	0,100	
7	9/32	13	0,51	16	240	70	2,75		0,150	0,100	
8	5/16	15	0,59	16	240	80	3,00		0,170	0,115	
10	3/8	17	0,67	16	240	100	4,00		0,210	0,140	
13	1/2	20	0,79	16	240	120	4,75		0,250	0,170	
16	5/8	24	0,94	16	240	160	6,25		0,350	0,235	
19	3/4	27	1,06	16	240	190	7,50		0,400	0,270	
25	1	35	1,38	16	240	250	10,00		0,730	0,495	
NA	LA	NEU	EMEA	SA	AP	AU					



671AA

Fuel-oil delivery 16 bar (240 psi)

Tube: Black NBR

Reinforcement: High tensile textile cords

Cover: Black synthetic rubber - abrasion, ozone and hydrocarbon resistant

Use: General purpose fuel and oil delivery

Safety factor: 3:1

Temperature: -25 °C +80 °C (-13 °F +176 °F)