



UNITRIX® 60

The multi purpose hose



Marking: 6 tobacco brown coloured axial markings on black cover,
PHOENIX UNITRIX 60 DN 10 R $10^6 \Omega/m$ Made in Germany

Application:

The multi purpose hose UNITRIX® 60 provides best results when used in the areas of mechanical engineering, farming, forestry, garages, quarries, construction sites as well as shipbuilding and the railway industry. It can be used with compressors, barrel pumps and aggregates. It can also be used in the areas of the mineral oil industry and the chemical and petrochemical industry.

UNITRIX® 60 is the right hose for conveying benzine, mineral oil, gasoil, kerosene, fuel oil, motor oil, compressed air, cold and hot water with or without detergent additives, vegetable oils, animal fats, propane, butane, diluted acids, technical alcohols, pesticides, salt solutions, naphtha.

Description:

- ▶ black, non-porous and smooth NBR lining
- ▶ working pressure up to 20 bar
- ▶ temperature range from - 25°C up to +85°C
- ▶ reinforcements: synthetic fibres
- ▶ highly flexible, robust
- ▶ NBR-cover, resistant to oil, grease and chemicals
- ▶ electrically conductive

Technical data:

Nominal width Zoll/Inch	Inner-Ø mm	Wall thickness mm	Working pressure* bar	Minimum Burst pressure* bar	Minimum bending radius approx. mm	Weight approx. g/m
1/4	6	3,5	20	60	35	160
5/16	8	3,75	20	60	50	210
3/8	10	3,75	20	60	60	250
1/2	13	4,0	20	60	80	320
5/8	16	4,5	20	60	100	430
3/4	19	5,0	20	60	120	550
1	25	5,5	20	60	150	760

* based on room temperatur

Delivery in coils of 50m

Continental
CONTITECH

OP DEN VELDE  **INDUSTRIE**