




12.440 PHANTOM HSS Spiraalboor

DIN 345N, con. schacht, gefreesde en geslepen uitvoering, met verdunde punt vanaf 14 mm, tophoek 118°.



T.b.v. materiaalsoort:




Artikelnr.	d1	l1	l2	d2	Artikelnr.	d1	l1	l2	d2	Artikelnr.	d1	l1	l2	d2
12.440.0325*	3,25	117	36	MK 1	12.440.1750	17,5	228	130	MK 2	12.440.3100	31	301	180	MK 3
12.440.0375*	3,75	120	39	MK 1	12.440.1775	17,75	228	130	MK 2	12.440.3125	31,25	301	180	MK 3
12.440.0400*	4	124	43	MK 1	12.440.1800	18	228	130	MK 2	12.440.3150	31,5	301	180	MK 3
12.440.0475*	4,75	133	52	MK 1	12.440.1825	18,25	233	135	MK 2	12.440.3200	32	334	185	MK 4
12.440.0500	5	133	52	MK 1	12.440.1850	18,5	233	135	MK 2	12.440.3250	32,5	334	185	MK 4
12.440.0525*	5,25	133	52	MK 1	12.440.1875	18,75	233	135	MK 2	12.440.3300	33	334	185	MK 4
12.440.0550	5,5	138	57	MK 1	12.440.1900	19	233	135	MK 2	12.440.3350	33,5	334	185	MK 4
12.440.0575*	5,75	138	57	MK 1	12.440.1925	19,25	238	140	MK 2	12.440.3400	34	339	190	MK 4
12.440.0600	6	138	57	MK 1	12.440.1950	19,5	238	140	MK 2	12.440.3450	34,5	339	190	MK 4
12.440.0625	6,25	144	63	MK 1	12.440.1975	19,75	238	140	MK 2	12.440.3500	35	339	190	MK 4
12.440.0650	6,5	144	63	MK 1	12.440.2000	20	238	140	MK 2	12.440.3550	35,5	339	190	MK 4
12.440.0675	6,75	150	69	MK 1	12.440.2025	20,25	243	145	MK 2	12.440.3600	36	344	195	MK 4
12.440.0700	7	150	69	MK 1	12.440.2050	20,5	243	145	MK 2	12.440.3650	36,5	344	195	MK 4
12.440.0725*	7,25	150	69	MK 1	12.440.2075	20,75	243	145	MK 2	12.440.3700	37	344	195	MK 4
12.440.0750	7,5	150	69	MK 1	12.440.2100	21	243	145	MK 2	12.440.3750	37,5	344	195	MK 4
12.440.0775	7,75	156	75	MK 1	12.440.2125	21,25	248	150	MK 2	12.440.3800	38	349	200	MK 4
12.440.0800	8	156	75	MK 1	12.440.2150	21,5	248	150	MK 2	12.440.3850	38,5	349	200	MK 4
12.440.0825	8,25	156	75	MK 1	12.440.2175	21,75	248	150	MK 2	12.440.3900	39	349	200	MK 4
12.440.0850	8,5	156	75	MK 1	12.440.2200	22	248	150	MK 2	12.440.3950	39,5	349	200	MK 4
12.440.0875	8,75	162	81	MK 1	12.440.2225	22,25	248	150	MK 2	12.440.4000	40	349	200	MK 4
12.440.0900	9	162	81	MK 1	12.440.2250	22,5	253	155	MK 2	12.440.4050	40,5	354	205	MK 4
12.440.0925	9,25	162	81	MK 1	12.440.2275	22,75	253	155	MK 2	12.440.4100	41	354	205	MK 4
12.440.0950	9,5	162	81	MK 1	12.440.2300	23	253	155	MK 2	12.440.4150	41,5	354	205	MK 4
12.440.0975	9,75	168	87	MK 1	12.440.2325	23,25	276	155	MK 2	12.440.4200	42	354	205	MK 4
12.440.1000	10	168	87	MK 1	12.440.2350	23,5	276	155	MK 3	12.440.4250	42,5	354	205	MK 4
12.440.1025	10,25	168	87	MK 1	12.440.2375	23,75	281	160	MK 3	12.440.4300	43	359	210	MK 4
12.440.1050	10,5	168	87	MK 1	12.440.2400	24	281	160	MK 3	12.440.4350	43,5	359	210	MK 4
12.440.1075	10,75	175	94	MK 1	12.440.2425	24,25	281	160	MK 3	12.440.4400	44	359	210	MK 4
12.440.1100	11	175	94	MK 1	12.440.2450	24,5	281	160	MK 3	12.440.4450	44,5	359	210	MK 4
12.440.1125	11,25	175	94	MK 1	12.440.2475	24,75	281	160	MK 3	12.440.4500	45	359	210	MK 4
12.440.1150	11,5	175	94	MK 1	12.440.2500	25	281	160	MK 3	12.440.4550	45,5	364	215	MK 4
12.440.1175	11,75	175	94	MK 1	12.440.2525	25,25	286	165	MK 3	12.440.4600	46	364	215	MK 4
12.440.1200	12	182	101	MK 1	12.440.2550	25,5	286	165	MK 3	12.440.4650	46,5	364	215	MK 4
12.440.1225	12,25	182	101	MK 1	12.440.2575	25,75	286	165	MK 3	12.440.4700	47	364	215	MK 4
12.440.1250	12,5	182	101	MK 1	12.440.2600	26	286	165	MK 3	12.440.4750	47,5	364	215	MK 4
12.440.1275	12,75	182	101	MK 1	12.440.2625	26,25	286	165	MK 3	12.440.4800	48	369	220	MK 4
12.440.1300	13	182	101	MK 1	12.440.2650	26,5	286	165	MK 3	12.440.4850	48,5	369	220	MK 4
12.440.1325	13,25	189	108	MK 1	12.440.2675	26,75	291	170	MK 3	12.440.4900	49	369	220	MK 4
12.440.1350	13,5	189	108	MK 1	12.440.2700	27	291	170	MK 3	12.440.4950	49,5	369	220	MK 4
12.440.1375	13,75	189	108	MK 1	12.440.2725	27,25	291	170	MK 3	12.440.5000	50	369	220	MK 4
12.440.1400	14	189	108	MK 1	12.440.2750	27,5	291	170	MK 3	12.440.5100	51	412	225	MK 5
12.440.1425	14,25	212	114	MK 2	12.440.2775	27,75	291	170	MK 3	12.440.5200	52	412	225	MK 5
12.440.1450	14,5	212	114	MK 2	12.440.2800	28	291	170	MK 3	12.440.5300	53	412	225	MK 5
12.440.1475	14,75	212	114	MK 2	12.440.2825	28,25	296	175	MK 3	12.440.5400	54	417	230	MK 5



12.440 PHANTOM HSS Spiraalboor

DIN 345N, con. schacht, gefreesde en geslepen uitvoering, met verdunde punt vanaf 14 mm, tophoek 118°.



T.b.v. materiaalsoort:



Artikelnr.	d1	l1	l2	d2	Artikelnr.	d1	l1	l2	d2	Artikelnr.	d1	l1	l2	d2
12.440.1500	15	212	114	MK 2	12.440.2850	28,5	296	175	MK 3	12.440.5500	55	417	230	MK 5
12.440.1525	15,25	218	120	MK 2	12.440.2875	28,75	296	175	MK 3	12.440.5600	56	417	230	MK 5
12.440.1550	15,5	218	120	MK 2	12.440.2900	29	296	175	MK 3	12.440.5700	57	422	235	MK 5
12.440.1575	15,75	218	120	MK 2	12.440.2925	29,25	296	175	MK 3	12.440.5800	58	422	235	MK 5
12.440.1600	16	218	120	MK 2	12.440.2950	29,5	296	175	MK 3	12.440.5900	59	422	235	MK 5
12.440.1625	16,25	223	125	MK 2	12.440.2975	29,75	296	175	MK 3	12.440.6000	60	422	235	MK 5
12.440.1650	16,5	223	125	MK 2	12.440.3000	30	296	175	MK 3	12.440.6300*	63	427	240	MK 5
12.440.1675	16,75	223	125	MK 2	12.440.3025	30,25	301	180	MK 3	12.440.6800*	68	437	250	MK 5
12.440.1700	17	223	125	MK 2	12.440.3050	30,5	301	180	MK 3	12.440.8500*	85	519	265	MK 6
12.440.1725	17,25	228	130	MK 2	12.440.3075	30,75	301	180	MK 3	12.440.9000*	90	529	275	MK 6

* De voorraad van dit artikel wordt niet meer aangevuld.