




84.879 TORAX Boorbus

DIN 179A, korte uitvoering, in- en uitwendig geslepen, geheel gehard, tolerantie op de boringsdiameter F7, tolerantie op de buitendiameter n6.



Artikelnr.	d1	d2	l1	Artikelnr.	d1	d2	l1
84.879.0120 - 84.879.0180	1,2 - 1,8	4	6	84.879.1525 - 84.879.1800	15,25 - 18	26	16
84.879.0190 - 84.879.0260	1,9 - 2,6	5	6	84.879.1825 - 84.879.2200	18,25 - 22	30	20
84.879.0270 - 84.879.0330	2,7 - 3,3	6	8	84.879.2225 - 84.879.2600	22,25 - 26	35	20
84.879.0340 - 84.879.0400	3,4 - 4	7	8	84.879.2625 - 84.879.3000	26,25 - 30	42	25
84.879.0410 - 84.879.0500	4,1 - 5	8	8	84.879.3025 - 84.879.3500	30,25 - 35	48	25
84.879.0510 - 84.879.0600	5,1 - 6	10	10	84.879.3550 - 84.879.4200	35,5 - 42	55	30
84.897.0610 - 84.879.0800	6,1 - 8	12	10	84.879.4300 - 84.879.4800	43 - 48	62	30
84.879.0810 - 84.879.1000	8,1 - 10	15	12	84.879.4900 - 84.879.5500	49 - 55	70	30
84.879.1010 - 84.879.1200	10,1 - 12	18	12	84.879.6000 - 84.879.6200	60 - 62	78	35
84.879.1210 - 84.879.1500	12,1 - 15	22	16	84.879.6500	65	85	35

