



Fußgerechte Sicherheit

From range:



**Article 8211 Lennard
Boot S3
with overcap**

Upper	<p>Grained leather, black, softly padded edge</p> <p><i>Lining:</i> climate regulating textile lining</p> <p><i>Tongue:</i> closed padded</p> <p><i>Lacing:</i> flat laces black/yellow</p> <p><i>Closing parts:</i> corrosion resistant metal eyelets</p>
Plus	<p>Overcap for protection during kneeling activities, reflective stripes at the side</p>
Outsole	<p>PU/PU-sole grey/black</p> <p>PU-midsole, reduces stress on joints and spine due to its damping impact</p> <p>PU-outsole: robust, slip resistant, heat resistant up to about 120°C, cold resistant up to about -20°C, steep front heel</p>
Insock	<p>Replaceable anatomically shaped insock</p>
Toecap	<p>Steel</p>
Anti-Penetration	<p>Steel</p>
Sizes/Width	<p>36 – 48 (Unisex) / 11</p>
Weight	<p>Approx. 630 g / piece (size 42)</p>
Designation	<p>According to EN ISO 20345:2011 S3</p>
Examples for use	<p>Areas for S2 in addition expected danger of stepping into sharp objects: Construction sector, sub construction sector, steel works, chemical industry, track construction</p>